

Certificate of Conformity of the Factory Production Control

2195-CPR-1428101

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR)*, this certificate applies to the construction product

Hot Rolled Products of Structural Steel

(tested for performance for the characteristics described in Annex 1 which is an inseparable part of this certificate)

produced by the manufacturer

EREĞLİ DEMİR VE ÇELİK FABRİKALARI T.A.Ş.

Uzunkum No:7, 67330 Kdz. Ereğli / Zonguldak – Türkiye

and produced in the manufacturing plant

EREĞLİ DEMİR VE ÇELİK FABRİKALARI T.A.Ş.

Uzunkum No:7, 67330 Kdz. Ereğli / Zonguldak – Türkiye

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 10025-1:2004

It is proof that the performance characteristics specified in the audit report numbered CPR-031/26, which is an integral part of this certificate and is annexed to this certificate under system 2+, are implemented and that all requirements of the Factory Production Control determined for these performances are compliant. This certificate was first issued on 08.10.2014, renewed on 08.10.2026 and will remain valid as long as neither the harmonised standard, the construction product, the assessment and verification of constancy of performance methods nor the manufacturing conditions and factory production control in the factory are modified significantly, unless suspended or withdrawn by the notified factory production control certification body. The certificate is supported through annual surveillance audit and is reissued after each surveillance audit.

Validity Date : 08.10.2027

Period Validity Date : 08.10.2027

Şaban GEZER
Technical Regulation Manager



FR. CPR. 24 R:05

SZUTEST UYGUNLUK DEĞERLENDİRME A.Ş.

Tatlısu Mahallesi, Akif İnan Sk. No:1 Ümraniye 34774 İSTANBUL / TÜRKİYE

Szutest.com.tr

Certificate of Conformity of the Factory Production Control

2195-CPR-1428101

Annex 1

Intended uses;

To be used in metal structures or in composite metal and concrete structures.

Controlled Performance Characteristics;

- Dimension and Shape Tolerances,
- Yield Strength,
- Elongation,
- Tensile Strength,
- Impact Resistance,
- Weldability,
- Durability.

Quality according to EN 10025-2:2019	The products in the form of:	Sizes (mm)		
		Thickness	Width	Length
S235JR, S235J0, S235J2, S235JR(Cu), S235JRC, S235J2C+N, S235J2+N, S275JR, S275J0, S275J2, S275J2+N, S275JRC, S275J2C+N, S355JR, S355J0, S355J2, S355K2, S355JR+N, S355J0+N, S355J2C+N, S355J2+N, S355J2(Cu), E295, E335, E360	Coils	1,4-25,0	700-1600	-
	Sheets cut from coils	1,4-15,0	700-1600	1500-15000
	Shredded coils	1,5-6,0	62-533	-
	Plates	5,0-100,0	1000-3800	2000-14000

Quality according to EN 10025-3:2019	The products in the form of:	Sizes (mm)		
		Thickness	Width	Length
S275N, S275NL, S355N, S355NL, S420N, S420NL, S460N, S460NL	Coils	1,4-20,0	700-1600	-
	Sheets cut from coils	1,4-15,0	700-1600	1500-15000
	Plates	5,0-60,0	1000-3050	2000-14000

Quality according to EN 10025-4:2019+A1:2022'ye	The products in the form of:	Sizes (mm)		
		Thickness	Width	Length
S275M, S355M, S420M, S460M	Coils	2,1-25,0	700-1525	-
	Sheets cut from coils	2,1-15,0	700-1525	1500-15000

Quality according to EN 10025-5:2019	The products in the form of:	Sizes (mm)		
		Thickness	Width	Length
S355J2W	Coils	8,0-16,0	700-1525	-
	Sheets cut from coils	8,0-15,0	700-1525	2000-15000
	Plates	8,0-60,0	1000-3000	2000-12000

Note: Quality grade "S460N" and "S460NL" can be produced up to 20 mm thickness.

Şaban GEZER
Technical Regulation Manager

FR. CPR. 24 R:05